



RENZACCI UK
...BE THE BEST!



Goliath

Electric steam generators



GE-65 + 90 COMBI

Technical data	GOLIATH 25	GOLIATH 50	GOLIATH 65-90
Power	400/3+N/50*	400/3+N/50*	400/3+N/50*
Pump motor	0,6 Kw	0,6 Kw	0,6 - 2,2 Kw
Water feeding	tubo gomma Ø int. 13 mm	tubo gomma Ø int. 13 mm	tubo gomma Ø int. 13 mm
Steam drawing	1/2"	1/2"	1/2"
Boiler drain	1/2"	1/2"	1/2"
Boiler capacity	20 lt	30 lt	55 lt
Encumbrance	65 x 51 x 70 cm	80 x 75 x 75 cm	80 x 75 x 75 cm
Encumb. with tank	65 x 51 x 120 cm	80 x 75 x 130 cm	80 x 75 x 130 cm
Encumb. COMBI	65 x 51 x 190 cm	80 x 75 x 190 cm	80 x 75 x 190 cm
Gross weight	80 kg	140 kg	150 kg
Gross weight with tank	115 kg	185 kg	195 kg
Gross weight COMBI	206 kg	330 kg	340 kg
Overall dimensions	84 x 80 x 90 cm	84 x 80 x 90 cm	84 x 80 x 90 cm
Overall dimensions with tank	84 x 80 x 138 cm	84 x 80 x 138 cm	84 x 80 x 138 cm
Overall dimensions COMBI	84 x 80 x 220 cm	84 x 80 x 220 cm	84 x 80 x 220 cm

*other voltages by request

For manufacturing necessities the above-mentioned specifications are not binding



GE-25



GE-50 + serbatoio



GE-65



GE-90 + serbatoio

Model	Power (KW)	Steam production kg/h	Steam working pressure	BASIC	DELUXE	HEAVY DUTY	ENERGY SAVER	KIT COMBI
GOLIATH 25	10 12 15 18	13 16 20 25	5 bar	•	•	•		
GOLIATH 50	24 26 28 30 33 36	33 36 38 41 45 49	5 bar	•	•	•	•	•
GOLIATH 65	30 36 42 48	41 49 57 65	5 bar 7 bar	•		•	•	•
GOLIATH 90	54 60 66	74 82 90	5 bar 7 bar	•		•	•	•

Twin heating elements for Goliath 25, available upon request.
The generators 50 - 65 - 90 are built with twin heating elements as a standard.

Goliath

Electric steam generators, with electronic water level controls, designed and built for an easy and quick installation as well as durability. All components are easily accessible allowing simple, straightforward routine maintenance. These steam generators are built with high grade materials and conform to PED European Standards. GOLIATH steam generators are available in the following versions:

- BASIC:** recommended for 8 - 10 hours/day of operation.
- DELUXE:** recommended for 14 - 16 hours/day of operation.
- HEAVY DUTY:** recommended for 24 hours/day of operation.

The **GOLIATH 65 and 90** models are also available in a 7-bar working-pressure version, which is perfect to obtain optimal performance from a Shirt finisher, a Collar & Cuff Press and for our LAV PRESS Series with polished head.

The **ENERGY SAVER** device is built with an upgraded pump and solenoid valve, and with a special tank to supply hot water back to the boiler up to 90°C, allowing significant energy savings.

The **KIT COMBI** allows two similar steam generators to be mounted on top of each other, complete with feeding tank, thereby doubling its power and also its hourly steam production.

For models, powers and versions, see the corresponding chart.
Available options: Stainless Steel Feed & Condensate Return Tank – Casters with support.



+44 (020) 8579 2661

mail@renzacci.co.uk

www.renzacci.co.uk