



RENZACCI UK

...BE THE BEST!

hawo

Hawo Professional Garment Bagging Machines

Garment Bagging machinery for drycleaners, laundries, the garment industry, hotels and professional packaging companies.



These machines are able to be used with Bio-Degradable polythene – helping to protect garments as well as the environment.

These units are also available in manual and also automatic (air operated) versions:

HP630KST – Free Standing model, manually operated.

HP630KW – Wall Mounted mode, manually operated.

HP630KST-P – Free Standing Automatic Air Operated model, two push button operation.

HP630KW-P – Wall mounted, Automatic Air Operated model, two push button operation.



Floor Mounted Device **Hp 630 KST**
Wall mounted device **hp 630 KW**

Cleaned clothes can easily be wrapped (with hangers) in order to prevent them from getting dirty or dusty again. You can determine the length of the package helping to prevent wastage – only use what you need.

Hp 630 KST floor mounted device with manual operation.

Technical Data	Hp 630 KST
Sealing type	Impulse separate welding with shoulder form, length 2 x 300 mm
Film width	Max. 600 mm
Type of film	High- low pressure PE-Tube film
Film thickness	2 x 0.2 mm
Device	With vertical adjustment
Connection	230 V / 50 Hz
Power	180 VA
Dimensions W x D x H	800 x 580 x 2100 mm
Weight	48 kg

Technical Data	Hp 630 KW
Dimensions W x D x H	800 x 380 x 910 mm
Weight	40 kg



Floor Mounted Device **Hp630KST-BS+SZ**

Bottom sealer, lower welding device with automatic operation via cable pull.

Hp 630 KST-BS floor mounted device, bottom sealer with manual operation.

Bottom sealer	Hp 630 KST-BS+SZ
Technical Data	Upper welding device same as Hp 630 KST
Sealing type	Impulse welding seam 3 mm, length 630 mm
Device	With vertical adjustment from top welding seam from 450 - 1450 mm
Connection	230 V / 50 Hz
Power	450 VA
Dimensions W x D x H	820 x 820 x 2250 mm
Weight	80 kg



Floor Mounted Device **Hp 630 KST-P**
Wall mounted device **Hp 630 KW-P**
Floor Mounted Device **Hp630KST-BS+SZ**

Hp630KST-P and **Hp630KW-P** are floor and wall mounted automatic bagging machines, head closing utilising two push button pneumatic switches.

Technical Data | Same as Hp 630 KST

Pneumatics	
Air consumption	max. 0.9 l / cycle
Connection	6 bar



Desktop unit **Hp 500 TM**

The ideal funnel-welding device for efficient packaging of your goods on the counter. The goods are packaged (clean) hygienic, dustfree and transparent.

Technical Data	Hp 630 KST
Film width	500 mm max
Film thickness	0.2 mm max
Sealing type	separate welding
Connection	230 V / 50 Hz
Power	180 VA
Dimensions W x D x H	500 x 800 x 400 mm
Weight	25 kg
Funnel	Chrome steel